

Modus Technical Specifications

Manufacturer	İnceler Medikal Sağlık Hiz. San. Tic. Ltd. Şti.		
Model	Modus®		
User Mode	Single, Continuous, Auto, Burst		
Compressed Air Supply	Internal Compressor, Portable model		
Average Pressure	1 to 5 bars		
Frequency of use	1-22 Hz		
Power Supply	100 – 240 VAC, 50/60 Hz, 50 W		
Fuses	2 x 1 A, 230 VAC		
Display	TFT Touch screen		
Treatment Start / Stop	Main Unit Button, Handpiece Button and Optional Foot Pedal		
Memory	3 - User defined		
Ready treatment protocol	20		
User Password	Yes		
Insulation	Internal 12 V DC transformer insulation		
HANDPIECE	SUSPENSION SYSTEM, 3 million shock pulses (3.000.000 SHOCK)		
	Applicators		
	Ø 6 mm	Radial	P. Depth 0-90 mm
	Ø 10 mm	Radial	P. Depth 0-85 mm
	Ø 15 mm	Radial	P. Depth 0-45 mm
	Ø 15 mm	Trigger	P. Depth 0-80 mm
	Ø 15 mm	Focus	P. Depth 0-60 mm
	Ø 20 mm	Radial	P. Depth 0-50 mm
	Ø 35 mm	Radial	P. Depth 0-75 mm
Weight	10 kg		
Dimensions	320mm X 390mm X 120mm		Control Unit
Classification	Conforms to EN 60601-1 criteria.		
	Class 1 Applied Part BF		
	IP 20 (Foot Pedal IPX5)		
	MDD 93/42 CEE Class IIb		
	EMC Tests Report No. LVT, Ankara		
Custom treatment protocol selections	YES		
Operating environment	10°C ≤ temperature ≤ 30°C		
	30% ≤ humidity ≤ 75%		
	700 hPa ≤ atmospheric pressure ≤ 1060 hPa		
Storage and Carriage Conditions	-10°C ≤ temperature ≤ +40°C		
	10% ≤ humidity ≤ 95%		
	500 hPa ≤ atmospheric pressure ≤ 1060 hPa		

Modus Technical Specifications

Modus-Eswt Set

Modus Main Unit	1 Unit
Handpiece	1 Unit
Suspension System	
3 million shock pulses (3.000.000 shock)	
Applicators	6 Units
Ø 6 mm	P.Depth 0-95 mm
Ø 10 mm	P.Depth 0-45 mm
Ø 15 mm	P.Depth 0-45 mm
Ø 15 mm-Trigger	P.Depth 0-60 mm
Ø 20 mm	P.Depth 0-50 mm
Ø 35 mm	P.Depth 0-50 mm
Soft Applicators	1 Unit
Compressor	Internal
Portable Carrying Bag	1 Unit
Trolley (Optionally)	1 Unit

